



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problem



POLY WRAP

HANGING PERFORMANCE BAFFLES

- **High Performance**
- **Lowest Cost**
- **Lightweight**
- **Standard Baffle has 2 grommets on one 4' side**

MATERIAL: Heat-sealed Polyethylene with Fiberglass fill.

FEATURES: Economical, multipurpose, high performance, lightweight.

APPLICATIONS: Gymnasiums, auditoriums, arenas & stadiums, manufacturing plants, machine enclosures, water treatment plants, animal hospitals and swimming pools.

THICKNESS: 1½".

SIZES: 2' x 4'.

WEIGHT: 1.6 lb/cu.ft density (2lbs each)

COLOR: Standard: White, Black

Optional: Beige, Blue, Silver Gray, Green, Purple, Teal, Yellow, Red, Burgundy.

FLAMMABILITY: Flame Spread: 8, Smoke Density: 0.

| Poly Wrap Baffles Baffle: Sabins/Baffle | 125Hz | 250Hz | 500Hz | 1KHz | 2KHz | 4KHz | NRC freq. avg. |
|--|-------|-------|-------|------|------|------|----------------|
| 2" | 2.1 | 6.5 | 10.7 | 14.1 | 12.7 | 8.1 | 11.0 |

